

## ZCLONE-Xi DRIVE ADAPTER GUIDE

INTERFACE	BUILT-IN/ADAPTER REQD	LOGICUBE ADAPTER	DESCRIPTION	MAX NUMBER USED PER Zxi	PHOTO
3.5" SAS	Built-in	N/A	Requires Optional Software	6 + 2 on expansion	
3.5" SATA	Built-in	N/A	Supported	6 + 4 on expansion	
2.5" SATA	Built-in	N/A	Supported	6+ 4 on expansion	
2.5" SAS	Built-in	N/A	Requires Optional Software	6+ 2 on expansion	
3.5" IDE	Use optional adapters	F-ADP-Z-2.5-IDE	SATA to 2.5/3.5" IDE Adapter	6 + 4 on expansion	
1.8" IDE	Use optional adapters	F-ADP-Z-1.8-IDE	1.8" IDE to SATA	6 + 4 on expansion	
2.5" IDE	Use optional adapters	F-ADP-Z-2.5-IDE	SATA to 2.5/3.5" IDE adapter	6 + 4 on expansion	
1.8" IDE ZIF	Use optional adapters	F-ADP-Z-ZIF-IDE	1.8" ZIF IDE to SATA adapter	6 + 4 on expansion	
eSATA	Use optional adapters	F-CBL-ESATA-Z	eSATA cable	6 + 4 on expansion	
microSATA	Use optional adapters	F-CABLE-MCRSATA	1.8" microSATA cable	6 + 4 on expansion	
mSATA	Use optional adapters	F-ADP-Z-MSATA	mSATA to SATA adapter	6 + 4 on expansion	
Flash drives	Use optional adapter	F-ADP-FLASH-RDR	Multi-card reader -connects via USB 3.0 port	3	
Compact Flash Drives	Use off-the-shelf CF to SATA adapter	Contact Logicube Technical Support	To connect CF drives directly to drive stations on the ZXi, users can purchase an off-the-shelf CF to SATA adapter. Contact Logicube Technical Support department for the specific model that has been tested and recommended for use with Zxi.	6+4 on expansion	N/A